

TM-21E



CAT III
600V



TM-22E



CAT III
600V



YF-8020



600A AC Clamp-On Meter

DISPLAY

- 3½ digits LCD with maximum reading 2000.
- Overload indication: "1"
- Low battery indication: "⎓"

FUNCTIONS

- TM-22E with True RMS measurements.
- Function keys:Data Hold.
- Test ranges:ACV,ACA,Ω.

600A True RMS AC Clamp-On Meter

600A AC Clamp - On Meter

DISPLAY

- 3½ digits LCD with maximum reading 2000.
- Low battery indication: "⎓"

FUNCTIONS

- Function keys:Data Hold.
- Test ranges:ACV,ACA,Ω.

Specifications

Model	TM-21E	TM-22E	YF-8020
Max measuring current	600A	600A	600A
Display counts	2000	2000	2000
Max conductor size	35mm	35mm	35mm
AC Current	0.01A~600A ±(1.5%+5)	0.01A~600A ±(1.5%+5)	0.01A~600A ±(2.0%+5)
AC Voltage	0.1V~600V ±(1.2%+5)	0.1V~600V ±(1.2%+5)	0.1V~750V ±(1.2%+3)
Resistance	1Ω~200KΩ ±(1.0%+2)	1Ω~200KΩ ±(1.0%+2)	1Ω~2KΩ ±(1.0%+2)
Size	218*75*43mm	218*75*43mm	209*77*36mm
Weight	About 335g	About 335g	About 260g
peak hold	—	—	—
Data hold	YES	YES	YES