

TM-16E



600A Autoranging AC Clamp-On Meter

- 3½ digits LCD with maximum reading 2000.
- Overload indication: "1".
- Low battery indication: "BAT".

FUNCTIONS

- Function keys: Data Hold(TM-16E/TM-23E) Select Range(TM-16E).
- Test ranges: ACV, ACA, DCV (TM-16E), Ω, Continuity(TM-16E/TM-23E) Diode (TM-16E).



TM-23E



Specifications

Model	TM-16E	TM-23E
Max measuring current	600A	600A
Display counts	2000	2000
Max conductor size	30mm	35mm
AC Current	0.1A~600A (Auto) ±(2.0%+5)	0.1A~600A ±(2.0%+5)
AC Voltage	0.1~600V ±(1.5%+5)	0.1~600V ±(1.5%+5)
DC Voltage	0.1V~600V ±(1.0%+2)	—
Resistance	0.1~200Ω ±(0.8%+3)	0.1~200Ω ±(0.8%+3)
Continuity buzzer	YES	YES
Diode	Test Volt 1.6VDC	—
Autorange	YES	YES
Auto power OFF	YES	—
Peak hold	—	—
Data hold	YES	YES
ACA(auto)	0.1A~400A	0.1A~400A
SIZE(L*W*H)	195*64*30	218*75*43
WEIGHT	240	335